

# LABORHITS

## Water Baths Hydro



Promocija  
**10%**  
1.9-30.9.2023.

### Features

- Interior made of high quality stainless steel
- Applications in the boiling range possible (temperature range: 25 to 100 °C)
- TFT color display for intuitive operation, temperature display in °C and °F
- Programmable timer
- Optical and acoustic alarm in the event of an error

The Hydro water baths are optimally equipped for every application in the laboratory. With their precise temperature distribution, they are designed for the needs of biological, medical or biochemical laboratories. The H 8 A and H 16 A models are also equipped with a circulation system for optional mixing.

Type	Capacity of the bath l	Internal dimensions (W x D x H) mm	External dimensions (W x D x H) mm	Rated capacity		PK	Cat. No.
					kW		
H 4	4	245 x 100 x 165	340 x 290 x 275		0.5	1	<b>4.672 291</b>
H 8	8	245 x 200 x 165	340 x 395 x 275		1.0	1	<b>4.672 292</b>
H 8 A	8	245 x 200 x 165	340 x 395 x 275		1.0	1	<b>4.672 297</b>
H 16	16	400 x 245 x 165	500 x 440 x 275		1.5	1	<b>4.672 293</b>
H 16 A	16	400 x 245 x 165	500 x 440 x 275		1.5	1	<b>4.672 298</b>
H 22	22	400 x 245 x 225	500 x 440 x 345		1.5	1	<b>4.672 294</b>
H 24	24	600 x 245 x 165	700 x 440 x 275		1.5	1	<b>4.672 295</b>
H 41	41	410 x 296 x 335	510 x 490 x 476		1.5	1	<b>4.672 296</b>

# LABORHITS

## Water Stills Puridest



### Features

- With »GFL Technology« for the highest quality, reliability and durability
- Distillates with conductance values up to 1.6  $\mu\text{S}/\text{cm}$ , comply with the DAB regulations and the provisions of international pharmacopoeias
- R series has a built-in storage tank
- Maintenance needs are limited to simply cleaning contaminants from the still
- With LED indicators for operating status and cleaning requirements (PD 2 and PD 4 only with LED indicators for operating status)

The water stills Puridest produce high-purity, low-gas, germ-free and pyrogen-free distillate, e.g. for diluting reagents and samples. After a direct connection to the raw water and the power supply, ultrapure water can be drawn off directly. The distillation systems with one or two distillation stages achieve excellent conductivity values. The glass water stills deliver water that is almost free of metal ions.

Type	Output L/hr.	*Conductance of the Mono distillate at 25 °C	*Conductance of the Bi distillate at 25 °C	Material	Dimensions (W x D x H) mm	PK	Cat. No.
PD 2	2	2.3 $\mu\text{S}/\text{cm}$		stainless steel	280 x 250 x 490	1	9.910 680
PD 4	4	2.3 $\mu\text{S}/\text{cm}$		stainless steel	280 x 250 x 490	1	9.910 681
PD 2 R	2	2.3 $\mu\text{S}/\text{cm}$		stainless steel	540 x 290 x 420	1	9.910 682
PD 4 R	4	2.3 $\mu\text{S}/\text{cm}$		stainless steel	620 x 330 x 460	1	9.910 683
PD 2 G	2	2.2 $\mu\text{S}/\text{cm}$		glass	650 x 200 x 390	1	9.910 686
PD 4 G	4	2.2 $\mu\text{S}/\text{cm}$		glass	650 x 200 x 390	1	9.910 687
PD 2 D	2	2.2 $\mu\text{S}/\text{cm}$	1.6 $\mu\text{S}/\text{cm}$	stainless steel/glass	500 x 260 x 470	1	9.910 689
PD 2 DG	2	2.2 $\mu\text{S}/\text{cm}$	1.6 $\mu\text{S}/\text{cm}$	glass	650 x 365 x 390	1	9.910 692

\*Conductances are „approximate“ values, depending on the raw water