

## Peristaltic pump LLG-uniPERISTALTICPUMP 1

Promocija  
**230,00€**  
do  
31.03.2022.



### The extra compact peristaltic pump

**The extra compact peristaltic pump.** Ideal for continuous dosing applications. Space-saving, robust and with a wide range of easily exchangeable pump heads.

- Stable flow rates
- **Compact design**
- Reversible working direction
- Pump heads easily exchangeable
- Various pump heads with different hose diameters available as accessory
- Low power consumption
- Corrosion-resistant ABS housing
- OLED display for indication of speed and working direction

**Scope of supply:** Pump, pump head, Pharmed® hose connectors 3 mm ID, 5 mm AD

#### Specifications

Speed range:	0.1 ... 150 rpm
Speed accuracy:	±0.1 rpm
Flow rate range:	0.004 ... 63.69 ml/min
Weight:	0.8 kg
Dimensions (W x D x H):	180 x 115 x 125 mm
IP code:	IP 31
Working temperature range:	0 ... 40 °C
Max. humidity:	80 %
Power rating:	10 W
Power supply:	100 ... 240 V, 50/60 Hz

Type	Plug type	PK	Cat. No.
LLG-uniPERISTALTICPUMP 1	EU	1	6263540*LLG
LLG-uniPERISTALTICPUMP 1	UK	1	6263541*LLG

## Peristaltic pump LLG-uniPERISTALTICPUMP 3

Promocija  
**290,00€**  
do  
31.03.2022.



- The peristaltic pump with high pumping capacity
- High pumping capacity of 398 ml/min

**The peristaltic pump with high pumping capacity.** Ideal for continuous dosing applications. Space-saving, robust and with stable flow rate.

- **High pumping capacity of 398 ml/min**
- Reversible working direction
- Hose connectors easily exchangeable
- Low power consumption
- Corrosion-resistant ABS housing
- OLED display for indication of speed and working direction

**Scope of supply:** Pump, pump head, Pharmed® hose connectors 6.4 mm ID, 9.6 mm AD

#### Specifications

Speed range:	0.1 ... 150 rpm
Speed accuracy:	±0.1 rpm
Flow rate range:	0.08 ... 398 ml/min
Weight:	0.8 kg
Dimensions (W x D x H):	190 x 128 x 135 mm
IP code:	IP 31
Working temperature range:	0 ... 40 °C
Max. humidity:	80 %
Power rating:	20 W
Power supply:	100 ... 240 V, 50/60 Hz

Type	Plug type	PK	Cat. No.
LLG-uniPERISTALTICPUMP 3	EU	1	6263550*LLG
LLG-uniPERISTALTICPUMP 3	UK	1	6263551*LLG

## Peristaltic pump tubing Tygon® LMT-55 with 2 colour-coded bridges



With 2 colour-coded bridges (international standards). Shore: 55. Fits most common peristaltic pump models. Standard tubing, transparent. Length 380 mm. Long working lifespan. Good resistance to acids and alkalis. Food-safe.



Colour	Int. diam. mm	Wall thickness mm	PK	Cat. No.
black-black	0.76	0.85	12	9208207*LLG
orange-orange	0.89	0.85	12	9208208*LLG
white-white	1.02	0.85	12	9208209*LLG
red-red	1.14	0.85	12	9208210*LLG
yellow-blue	1.52	0.85	12	9208219*LLG
blue-blue	1.65	0.85	12	9208213*LLG
green-green	1.85	0.85	12	9208214*LLG
purple-purple	2.06	0.85	12	9208215*LLG
purple-white	2.79	0.85	12	9208218*LLG
black-white	3.18	0.85	12	9208222*LLG