

## LABORTOPS

valid until 30.06.2020

LLG-uni PERIPUMP 1 and 3



**NEW**



Space-Saving  
and Robust  
Peristaltic Pumps

**Novo  
u LLG  
portfoliju**

## Peristaltic Pump LLG-uni

PERIPUMP 1

**!** Easily Exchangeable Pump Heads  
Up to 150 ml/min



**NEW**



Promocija  
**250€**

The extra compact peristaltic pump. Ideal for continuous dosing applications. Space-saving, robust and with a wide range of easily exchangeable pump heads.

- Stable flow rates
- Compact design
- Reversible working direction
- Pump heads easily exchangeable
- Various pump heads with different hose diameters available as accessory
- Low power consumption
- Corrosion-resistant ABS housing
- OLED display for indication of speed and working direction

Scope of supply: Pump, pump head,  
Pharmed \* hose with connection 3 x 1 mm

Specifications	
Speed range:	0.1 ... 150 min <sup>-1</sup>
Speed accuracy:	± 0.1 min <sup>-1</sup>
Flow rate range:	0.004 ... 149.23 ml/min
Weight:	0.8 kg
Dimensions (W x D x H):	180 x 115 x 125 mm
IP code:	IP 31
Working temperature range:	0 ... 40 °C
Max. humidity:	80 %
Power rating:	10 W
Power supply:	100 ... 240 V, 50/60 Hz

Type	Plug type	PK	Cat. No.
LLG-uni PERIPUMP 1	EU	1	6263540*LLG
LLG-uni PERIPUMP 1	UK	1	6263541*LLG

## Peristaltic Pump LLG-uni

PERIPUMP 3

**!** High Pump Capacity  
Up to 930 ml/min



Promocija  
**300€**

The peristaltic pump with high pumping capacity. Ideal for continuous dosing applications. Space-saving, robust and with stable flow rate.

- High pumping capacity of 930 ml/min
- Reversible working direction
- Hose connectors easily exchangeable
- Low power consumption
- Corrosion-resistant ABS housing
- OLED display for indication of speed and working direction

Scope of supply: Pump, pump head,  
Pharmed \* hose connectors 6.4 mm ID, 9.6 mm AD

Specifications	
Speed range:	0.1 ... 150 min <sup>-1</sup>
Speed accuracy:	± 0.1 min <sup>-1</sup>
Flow rate range:	0.08 ... 930 ml/min
Weight:	0.8 kg
Dimensions (W x D x H):	190 x 128 x 135 mm
IP code:	IP 31
Working temperature range:	0 ... 40 °C
Max. humidity:	80 %
Power rating:	20 W
Power supply:	100 ... 240 V, 50/60 Hz

Type	Plug type	PK	Cat. No.
LLG-uni PERIPUMP 3	EU	1	6263550*LLG
LLG-uni PERIPUMP 3	UK	1	6263551*LLG

## Accessories for LLG-uni PERIPUMP 1 and 3



Description	For	PK	Cat. No.
Pumphead with PharMed * tubing ID 1 mm	LLG-uni PERIPUMP 1	1	6263542*LLG
Pumphead with PharMed * tubing ID 2 mm	LLG-uni PERIPUMP 1	1	6263543*LLG
Pumphead with PharMed * tubing ID 3 mm	LLG-uni PERIPUMP 1	1	6263544*LLG
Pharmed * tubing ID 1 mm with connector and Tube Clip	LLG-uni PERIPUMP 1	1	6263546*LLG
Pharmed * tubing ID 2 mm with connector and Tube Clip	LLG-uni PERIPUMP 1	1	6263547*LLG
Pharmed * tubing ID 3 mm with connector and Tube Clip	LLG-uni PERIPUMP 1	1	6263548*LLG
Pharmed * tubing (ID: 3.1 mm, OD: 6.3 mm) with connector and Tube Clip	LLG-uni PERIPUMP 3	1	6263552*LLG
Pharmed * tubing (ID: 6.4 mm, OD: 9.6 mm) with connector and Tube Clip	LLG-uni PERIPUMP 3	1	6263554*LLG

ID = Inner diameter, OD = Outer diameter